

IQZoom 95S

38-95mm POWER ZOOM

From Wide-angle to Close-ups,
Ideal Framing is at Your Finger Tips!

Experiment with the 95mm telephoto for up close
and personal shots. Try the 38mm wide-angle setting
and capture the subject against a larger background.
Shoot your subject with more natural perspectives.



38mm ↔ 95mm



PENTAX IQZoom 95S Specifications

Type: 35mm fully automatic lens-shutter camera with built-in zoom lens, autofocus, auto exposure control and auto flash.
Flash: 35mm DX-coded film with 24mm x 36mm format.
Lens: PENTAX power zoom 38mm -95mm f/4.5 - f/10 lens; 5 elements in 5 groups.
Focusing System: PENTAX infrared active autofocus system.
Autofocusing Range: 2.6ft. (0.8m) to infinity.
Exposure Control: Programmed auto exposure control.
Metering Range: (1) Shooting in auto mode: EV10 - EV17.3 (38mm at ISO 400). EV13.3 - EV19 (95mm at ISO 400).
(2) Slow shutter speed and backlight compensation: EV8 - EV17.3 (38mm at ISO 400) EV8 - EV19 (95mm at ISO 400)
Shutter: Programed AE electronic lens shutter. Shutter Speed: approx. 1/360 sec. to 2 sec; 1/2 sec. to 1 min. in bulb mode.
Viewfinder: Actual-image zoom viewfinder.
Viewfinder Area: 83% (at 10ft.). Indication: Focus and flash status, close distance compensation frame and AF frame.
External LCD Indication: Exposure counter, battery exhaustion warning, red-eye reduction, flash-on, flash-off, slow-speed shutter, bulb, bulb, back light compensation, Infinity-landscape and self-timer.
Film Loading: automatic film loading with first-frame positioning.
Film Winding: Automatic film winding. (Single-frame).
Film Rewinding: Automatic film rewinding at the end of roll. Automatic stop upon rewind completion. (Mid-roll rewinding possible).
Film-Speed Setting: Auto film-speed setting with DX-coded film from ISO 25 - 3200.
Self-Timer: 10-second delay electronic self-timer.
Flash: Built-in flash. Automatic discharge under low lighting conditions in auto mode. Flash-on and flash-off modes. Daylight-sync, slow-shutter sync. and bulb sync available.
Recycle Time: Approx. 7 sec. with fresh lithium battery.
effective Range: (1) 2.6ft. - 24.6ft. (0.8m - 7.5m) (38mm at ISO 400)
(2) 2.6ft. - 11.2ft. (0.8m - 3.4m) (95mm at ISO 400)
Red-eye reduction lamp when red-eye reduction feature is in use.
Power Source: One 3V lithium battery (CR123A or DL123A type).
Dimensions and Weight: 4.7 (W) x 2.8 (H) x 2.1 (D) inch, (120.5 x 70.5 x 53.5mm). 8.6 oz. (245g) without battery.

IQZoom 95S Date
Data Imprinting: Five-mode switchable: "Year-Month-Day," "Month-Day-Year," "Day-Month-Year," "Day-Hour-Minute" and blank.
Dimensions and Weight: 4.7 (W) x 2.8 (H) x 2.1 (D) inch, (120.5 x 70.5 x 56mm). 8.8 oz. (250g) without battery.

- Design and specifications are subject to change without notice.
- Use of film with ISO 400 or faster is recommended with this camera.
- It is strongly recommended that you read the entire operation manual before operating this camera.
- PENTAX and IQZoom are registered trademarks of Asahi Optical Co., Ltd. registered at U.S. Patent and Trademark Office.

PENTAX®
National Sales & Service Headquarters
Pentax Corporation
35 Inverness Drive East
Englewood, CO 80112

Post Office Box 6509
Englewood, CO 80155-6509
(303) 799-8000

PENTAX

IQZoom 95S

38-95mm Compact Zoom Point-and-Shoot
Camera Encased in a Stylish Body





IQZoom 95S– The Compact Zoom with Stylish Looks and High Performance!
Featuring lots of easy-to-use high-performance functions, the versatile and compact IQZoom 95S is point-and-shoot photo fun. Day or night, indoors or out, it is ready to capture quality pictures in style.



IQZoom 95S

AUTO BACKLIGHT COMPENSATION



Backlight Compensation Mode
A bright background or shade can result in the subject of the photo appearing darker. The backlight compensation mode gives you a bright and beautiful photo without having to use a flash.

BULB MODE

Open the Shutter and Capture the Night
Bulb mode lets you keep the shutter open for up to one minute, enabling you to capture the vivid colors, motion and drama of illuminated night scenes.



RED-EYE REDUCTION

Minimize "Red-Eye" Effect
This handy mode can reduce the annoying phenomenon of "red-eye" that occurs when using normal flash.*

*This mode does not eliminate "red-eye" effect in all instances.



LCD PANEL

Information at a Glance
Using simple icons, the easy-to-see LCD panel displays the status of a camera at a glance.



ZOOM VIEWFINDER

"Actual Image" Preview
The actual-image zoom viewfinder automatically displays the framing area according to the zoom ratio for quick and precise photo composition.



IQZoom 95S DATE
You may now print the date or day and time on your photographs by using the date version of the IQZoom 95S. There are four different imprint settings as well as a blank one to choose from.