

Ciro-flex



INSTRUCTION MANUAL

GUARANTEE *and Service Benefits*

"We warrant each new Ciro-flex to be free from defects in factory workmanship or material under normal use and service. Our obligation under this warranty is limited to repairing or exchanging any defective part or parts, if the Ciro-flex is returned to us, either directly or through our distributors or dealers, transportation to and from the factory to be assumed by the purchaser, within one year from the date the Ciro-flex is sold to the original purchaser.

"This warranty does not apply if, in our judgment, this Ciro-flex has been misused, abused, or used otherwise than in accordance with the instructions supplied with each unit, or if the camera is repaired by an unqualified person.

"This warranty is in lieu of all other warranties expressed or implied, and no representative or person is authorized to assume for us any liability in connection with the sale or use of this Ciro-flex".

CIRO CAMERAS, INC.
425 South Sandusky St.
Delaware, Ohio

*Export Division: 23-25 Warren Street, NEW YORK 7, N. Y.
Cable Address: SIMONTRICE NEW YORK*

GETTING ACQUAINTED . . .

WELCOME to the ranks of satisfied Ciro-flex owners! You, like others who have turned to Ciro-flex, will find it a precision-built reflex camera capable of giving you consistently better, clearer, sharper pictures. Every part, every assembly used in its manufacture is the result of painstaking labor by highly skilled craftsmen whose job it is to give you the best camera possible for your photographic dollar.

So look upon your Ciro-flex as a fine instrument; care for it as such and it will repay you with a lifetime of more than satisfactory service.



This 2 1/4" x 3 1/4" print reproduction is the actual size of negatives you'll get with your Ciro-flex.

WORKING PARTS OF *Ciro-flex*

The first step in using any new camera is to familiarize yourself with its working parts. These parts of your new *Ciro-flex* are indicated below, while explanations of their use are presented on the opposite page.



- 1 **VIEWING HOOD:**—Snaps open by pressing release lever on left side. Ground glass panel beneath hood reflects actual print-size image of picture the camera sees. Magnifier inside hood provided for sharp, critical focusing. Small opening in back panel serves as Sports-finder for fast action shots.
- 2 **DEPTH-OF-FOCUS CHART:**—Accurately calibrated with marked focusing knob to establish a "zone of sharpness" at a given distance for a predetermined exposure setting. See page 11 for detailed explanation of use.
- 3 **WINDING KNOB:**—Rolls film forward to bring next exposure number under red window on back of camera.
- 4 **FOCUSING KNOB:**—Turns to bring image into sharp relief on ground glass. Marked for distances from three feet to infinity.
- 5 **VIEWING LENS:**—Fine coated f3.2 Wollensak Anastigmat lens synchronized with Taking Lens below to permit sharp focusing and excellent composition arrangements on the ground glass before each exposure.
- 6 **SHUTTERS:**—Your Ciro-flex is equipped with either Standard or "M-F" Synchronomatic Alphax Automatic Shutter with speeds from 1/10 to 1/200 of a second plus T. and B., or standard or "M-F" Synchronomatic Rapax Set-and-Release Shutter with speeds from 1 to 1/400 of a second plus T. and B. Both Synchronomatic shutters feature a special built-in mechanism that automatically provides synchronized flash at all speeds with Class F flashlamps, and at speeds marked in red on the shutter with Class M lamps.
- 7 **BUILT-IN FLASH FITTING:**—Conveniently located on right side of camera. Designed to fit standard types of flash synchronizer cords.
- 8 **TAKING LENS:**—85 mm f3.5 Wollensak Anastigmat taking lens fine coated and corrected for excellent color work. Matched and perfectly synchronized with viewing lens above. And both lenses are controlled by special automatic corrective parallax device.
- 9 **CABLE RELEASE FITTING:**—For convenient optional use whenever desired.

FILMS THAT FIT *Ciro-flex*

Your *Ciro-flex* takes either Eastman 120 or Ansco 120 for black-and-white prints while Eastman Kodacolor C-120 and Ansco Color Film 120 may be used for fine color work.

Eastman 120 and Ansco 120 are available in several different types or grades each of which, properly exposed, will record the full range of tone values.

Since some types of film are more sensitive to light than others, the specific "speed" of the film being used plus the intensity of light illuminating the subject should be considered in determining proper exposure settings.

The use of a good exposure meter is an excellent short-cut through the complications of correct exposure and it provides you with a selection of lens apertures and shutter speeds that will result in satisfactory negatives.

For your information as well as for a basis of film comparison, the published film speed ratings of each of the films that fit your *Ciro-flex* are reprinted below:



EASTMAN 120

FILM	General Electric		Wetzel	
	0	I	0	I
Super 22	125	100	100	84
Flex 2	84	48	58	32
Parachrome E	32	24	24	16
Super Ortho Press	64	32	58	32
Velocchrome	64	32	58	32
Kodacolor C-120	32	..	28*	..


ANSCO 120

FILM	General Electric		Wetzel	
	0	I	0	I
Superpan Press	125	100	100	84
Superpan	84	48	58	32
Parachrome	64	32	58	24
Color Film 120	15	15	15	15

*Indicates Tentative Values

LOADING YOUR *Ciro-flex*

Open the camera by pressing down on *Button A* and lifting out back cover panel. Mount the film in *Recess B* by (1) placing one end of the spool in *stationary Spool Holder C* and (2) swinging the other end in toward top of camera (see inset) and over spring-mounted spool holder at opposite side of *Recess B*.





LOADING (CONT'D)

Now break the seal and draw film up over *Focal Plane Opening D*, making sure that colored protecting paper on film is facing out. Slip pointed end of film through the long slot in Take-up Spool E as shown above and turn winding knob F a few times until film is tight on Take-up Spool.

Return back cover panel to closed position and lock in place by pushing in on back cover.

With camera loaded and back cover panel locked securely, turn Button G to open built-in Window H. Then turn Winding Knob until the figure (1) appears under red window.

To give film maximum protection from light, window should be kept closed at all times except when transporting film to next exposure number.

FOCUSING YOUR *Ciro-flex*

Your *Ciro-flex* was designed to bring you two separate systems of focusing, both of which serve a definite purpose . . . the Ground Glass System for sharp, critical focusing and general purpose use, and the Depth of Focus Scale System for sports events and fast moving objects.

While both systems are fully explained on the following pages, let's first establish a basis of understanding with regard to certain terms used in any discussion of this subject.

TERMINOLOGY

Diaphragm or Lens Stop

The diaphragm or lens stop is an adjustable iris located in the shutter between the lens elements. It controls the amount of light passed through the fine "wocoated" Wollensak taking lens used by *Ciro-flex*. It also serves as the device that controls the depth of focus in your *Ciro-flex*.



The picture you see
is the picture you take



Taken with Diaphragm Open



Taken with Diaphragm Closed

Depth-of-Focus . . .

When the lens is focused on a point or object, those subjects somewhat nearer and farther away from the lens are relatively sharp also. This effect is called "depth-of-focus". As the diaphragm is made smaller . . . i.e., as the lens is stepped down, you will note that this field of relatively sharp focus is extended to subjects even nearer and farther away from the object upon which the lens is focused as illustrated above.

Correct Exposure Setting . . .

The correct exposure setting for a given picture depends upon the intensity of the light with which the subject is illuminated and the speed of the film being used. When these quantities are known, the shutter may be adjusted to the proper diaphragm opening and set for the right length of time to result in sharp, clear negatives of a density which will permit making good prints.

With knowledge of film speed values, the use of a good exposure meter is recommended as an excellent short-cut to correct exposure settings.

FOCUSING . . . *Ground Glass System*

The *Ciro-flex* Ground Glass System of focusing gives you a print-size preview of every picture you take before you expose the film. It is used in most general cases where time permits and is particularly recommended for taking portraits and other pictures where sharp, clear, crispness of detail is desired.

To focus on the ground glass, open the viewing hood by pressing down on release lever on left side of camera. Now, by holding the camera in your left hand up close to your chest, you can look down onto the ground glass and see an actual print-size image of the picture the camera actually sees projected in full negative size ($2\frac{1}{4}" \times 2\frac{1}{4}"$).

Next step is to frame the image you see to obtain an interesting arrangement for picture composition. You may find it necessary to take a few steps forward or backward . . . or to raise or lower the camera to achieve a special angle effect.

After you have framed the picture you want, turn the focusing knob until the principal object in your picture image stands out in bright, sharp relief.

Whenever extra sharp, critical focusing is desired, the magnifying glass attached to top panel of viewing hood may be flipped into position over the ground glass image.



FOCUSING . . . *Ground Glass System*

Knowing the speed of the film you're using and estimating (or checking with a light meter) the intensity of the light on your subject, you then adjust the shutter to the correct exposure setting and cock the shutter. Check your ground glass once more to make sure of distance and composition, press up on the shutter release trigger and the picture is yours forever.

THE Ciro-flex SPORTSFINDER

The *Ciro-flex Sportsfinder* is a small opening in the back panel of the viewing hood to serve your need for fast-action sports shots. For sharper, clearer action prints, pre-focus on the ground glass as described above using some object where the action is to occur as your focal point.

Then press the front panel of the viewing hood down to the small catch lock on the back panel. Now, instead of looking through the ground glass, you merely raise the camera and "catch" the action through the Sportsfinder.

If time does not permit pre-focusing on the ground glass, the Sportsfinder may be used with the *Ciro-flex Depth-of-Focus Scale System* described on page 11.



FOCUSING . . . *Depth-of-Focus System*

The Ciro-flex Depth-of-Focus Scale is located on the camera-body just above the focusing knob. To use this scale, focus the camera as already explained or simply judge the distance between the camera lens and your subject.

After determining the correct exposure setting, read the footage distance on the focusing knob that falls between your diaphragm opening figures appearing on both sides of the zero line on the depth-of-focus scale.

This distance represents a "zone of sharpness" extending in front of and behind the focal point of your picture. Any objects within those limits will be relatively sharp on the negative.

For example, in the picture at right, the focus is set at 18 feet. If the diaphragm is set at $f/16$, the depth of focus—or "zone of sharpness"—extends 10 feet in front and 100 feet behind the focal point of your picture. Or, using $f/4$ diaphragm opening with focus set at 18 feet, the depth of focus extends from 15 feet to 22 feet.



THE *Ciro-flex* SNAPSHOT RULE

When taking ordinary snapshots, it is not always necessary to focus on the ground glass. By merely using the depth-of-focus scale, you can readily "set" your camera for a "zone of sharpness" and follow this famous *Ciro-flex* snapshot rule:

LENS SET AT

f.11

FOCUS SETTING
DISTANCE

10 feet for
closeups*

50 feet for
distant
scenes**

CLOSEUPS mean 8 ft. to 15 ft.

****DISTANT SCENES** mean 18 ft.
to infinity.

This rule is presented as a helpful guide to increase the usefulness of your *Ciro-flex*. In practice this rule permits you to carry your camera set at a "zone of sharpness" ready for instant use should a good subject appear unexpectedly. You need only set the shutter speed according to the brightness of the light and the kind of film used to insure good results.

RECOMMENDED ACCESSORIES

Ciro-flex Camera Case — Made of genuine cowhide attractively lined with dubonnet velvet. Designed to permit unrestricted use of the protected camera. Just drop the front cover as shown and you're ready for action.



Cable Release — Cable releases are available for use with your *Ciro-flex*. They are a valuable accessory for time or bulb exposures where a slight movement of the camera may ruin an excellent picture.

Flash Gun — Any flash attachment of standard make which will fit the Alphax or Rapax Shutters may be used with the *Ciro-flex*.

Tripod — Any tripod having a $\frac{1}{4}$ "-20 thread attachment will fit the *Ciro-flex*.

Filters — Any well-known make of filters in the 32mm. mount size will fit your *Ciro-flex* camera. For all practical purposes the medium yellow is recommended.

Portrait Lenses — Your dealer carries a selection of special lenses for fine portrait photography which will bring the image up closer than three feet. These supplementary lenses can be obtained in various focal lengths and should be mounted to fit the 32mm. diameter lens mount.

