

Konica



HEXAR *Classic*

A Special Version Of Konica's Award-Winning HEXAR, The First True Compact Alternative To SLRs

Limited Edition



Designed In Classic Silver And Black To Commemorate Konica's 120th Anniversary



HEXAR Classic

A Limited Edition Set Commemorating Konica's 120th Anniversary

- Comprises camera and metal lens cap, the dedicated HX-14 electronic flash, a leather strap, and a 24-shot roll of Konica Impresa 50 professional color negative film

Features

- Fast, high-density 2.0/f HEXAR lens
- Konica's innovative 3-eye PSD active AF system
- Dynamic Parallax compensation viewfinder
- Silent Mode

Extended Features

- Automatic infrared focal correction
- Multiple exposures
- Manual guide number setting
- One-touch exposure correction setting
- Auto exposure bracketing

Specifications

Model: 35mm lens shutter type camera with frame format of 24 x 36mm.

Lens: Konica Hexar lens of 35mm f/2.0 (6 groups 7 elements) with minimum aperture f/22. Built-in lens hood.

Focal Adjustment: Infrared 3-eye active autofocus system. Manual focus setting available by using focus indicator.

Shooting Range: 0.6m-∞

Shutter: Step-motor drive electromagnetic shutter (T, 30-1/250 sec.)

Film Sensitivity: Automatic setting for DX coded film (ISO 25-5000). Manual setting (ISO 6-6400).

Light Metering Range: SPD photocell used. Center weighted light metering at approximately 15 degrees (EV 0-16/ISO 100), and spot-metering at approx. 4 degrees (EV 3-18/ISO 100).

Exposure Adjustment (ISO 100): Three modes selectable using Main/Shooting Mode switch: P (Programmed AE) Mode for EV 7-16 (Camera-Shake Critical Speed at 1/30 sec.). A (Aperture Priority AE) Mode for EV 0-16 and M (Manual) Mode for EV 3-17 (Except T-exposure).

Viewfinder: Reverse Galileo type viewfinder with illuminated bright frame and automatic parallax compensation. Display in viewfinder with focus lock lamp and all data and warnings relevant to exposure and range metering.

Film Transport: Electrical frame advance driven by built-in motor and automatic rewinding with function for early rewind.

Self-timer: Electronical design with operating time of approx. 10 seconds. Cancellation possible after activation.

Display Panel: Number of frame exposed, shutter speed, aperture setting, film sensitivity, exposure compensation, battery check, etc.

Other Features: Focus lock function, exposure compensation (± 2 EV in 1/3 increments), silent mode, manual setting of camera-shake critical speed, automatic power off with timer and variable sync. shot function when used with dedicated flash.

Battery Life: Approx. 200 rolls (24 exposures).

Power: Camera: 1 x Lithium battery (2CR5: 6V).

Dimensions/Weight: 137.5 x 76.5 x 64.5mm (5-5/12 x 3.0 x 2-6/12 inches); 495g (17-5/12 oz.) without battery.

Performance is based on Konica test results. The specifications and appearance may change without notice.

Konica

KONICA CORPORATION No. 26-2, Nishishinjuku 1-chome, Shinjuku-ku, Tokyo 163, Japan Tel: (03) 3349-5121 KONICA U.S.A., INC. 440 Sylvan Avenue, Englewood Cliffs, N.J. 07632, U.S.A. Tel: (201) 568-3100 KONICA CANADA INC. 1329 Meyerside Drive, Mississauga, Ontario, L5T 1C9 Canada Tel: (416) 670-7722 KONICA EUROPE G.m.b.H. Industriezentrum X11, D-8011 Hohenbrunn, Germany Tel: (08102) 8040 KONICA U.K. LTD. Plane Tree Crescent, Feltham, Middlesex, TW13, 7HD, England Tel: (01) 751-6121 KONICA FRANCE Paris-Nord 11305 rue de la Belle Etoile B.P. 50077 95948 ROISSY C.D.G. CEDEX Tel: 49-38-65-50 KONICA NETHERLAND B.V. Kuiperbergweg 44, NL-1100 AJ Amsterdam Z.O., The Netherlands Tel: (020) 978701 KONICA GESELLSCHAFT m.b.H. Hofbauergasse 3, A-1120 Wien, Austria Tel: (0222) 834521 KONICA AUSTRALIA PTY. LTD. Unit B4, 1-3 Rodborough Road, Frenchs Forest, N.S.W. 2086, Australia Tel: (02) 452-5111 KONICA HONG KONG LTD. Room 1818, Sun Hung Kai Centre, 30 Harbour Road, Hong Kong Tel: (5) 757288 KONICA SINGAPORE PTE. LTD. 247 Alexandra Road #03-00, Singapore 0315 Tel: 473-1377 KONICA THAILAND CO., LTD. Suite No. 1305, B.B. Building, 54 Asoke Road, Sukhumvit 21, Bangkok 10110, Thailand Tel: 260-7114